




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup>:</b>  <b>E01B 19/00</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 99/15732</b>  <b>(43) International Publication Date:</b> 1 April 1999 (01.04.99)
<b>(21) International Application Number:</b> PCT/GB98/02767  <b>(22) International Filing Date:</b> 18 September 1998 (18.09.98)  <b>(30) Priority Data:</b> 9719864.2 19 September 1997 (19.09.97) GB  <b>(71) Applicants (for all designated States except US):</b> BRITISH STEEL PLC [GB/GB]; 15 Marylebone Road, London NW1 5JD (GB). UNIVERSITY OF SOUTHAMPTON [GB/GB]; Highfield, Southampton SO17 1BJ (GB).  <b>(72) Inventors; and</b> <b>(75) Inventors/Applicants (for US only):</b> HODGSON, William [GB/GB]; Spring Bank, Braithwaite, Keswick, Cumbria CA12 5RY (GB). CLARKE, John, Barry [GB/GB]; 6 Hall Crescent, Rotherham S60 3LQ (GB). FARRINGTON, David [GB/GB]; Blossom Hill Cottage, Morland, Penrith, Cumbria CA10 3AS (GB). THOMPSON, David, John [GB/GB]; 1 Victory Way, Rownhams, Southampton SO16 8LA (GB). JONES, Christopher, John, Cedric [GB/GB]; 1 Eldridge Gardens, Romsey, Hampshire SO51 7RT (GB).  <b>(74) Agents:</b> DOWNING, Michael, Philip et al.; Fry Heath & Spence, The Old College, 53 High Street, Horley, Surrey RH6 7BN (GB).		<b>(81) Designated States:</b> AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  Published <i>With international search report.</i>
<b>(54) Title:</b> RAIL FIXINGS		
<b>(57) Abstract</b>  <p>A damper (18) for reducing the track noise emitted by a rail system comprises a deformable material (20) attachable to a surface of the rail, incorporating a plurality of elongate discontinuous resonant members (22, 24) of a stiff material as compared to the deformable material, sized to contain at least two resonant frequencies in the range of interest. The resonant members (22, 24) are suitably of steel or other metallic material. They can be of different profile, to form a resonant system with at least two resonant frequencies in the relevant frequency range. They are suitably embedded in the deformable material (20), to ensure adequate vibrational transfer from the rail to the resonant members and also provide environmental protection. The deformable member (20) is visco-elastic, for example rubber or a rubber-like material. This may be preformed and glued to the rail (10), or it can be cured in place on the rail. The damper (18) is positioned on the rail (10) at the junction between the web (14) and the foot (16) of the rail. One resonant member (22, 24) can be an elongate angled section, the angle preferably matching the angle between external surfaces of the head (12) and foot (16). Another resonant member (22, 24) can be a solid elongate block, the external faces adjacent the web (14) and foot (16) being angled to match.</p>		



*FOR THE PURPOSES OF INFORMATION ONLY*

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

## RAIL FIXINGS

The present invention relates to rail fixings. It is more particularly concerned with rail fixings that exhibit advantageous noise characteristics.

The noise emitted by moving rail vehicles is a major limitation on their use, in that it will limit the ability of operators to install new lines in populated areas, and will limit speeds and traffic volumes on existing lines. The noise tends to be dominated by rolling noise from the wheel/rail interface, which is caused partly by vibration of the wheels and partly by vibration of the track.

It is not possible to select alternative materials, etc, for these elements since they are subject to very high transient loads during use, and must withstand these. Materials which would be able to absorb vibration and hence reduce noise would be unable to survive in use for any appreciable time. Resilient rail fastenings have been employed to reduce track forces and thereby reduce component damage and structure-borne noise. However, they have an adverse effect on track noise as they tend to reduce the attenuation of rail vibration.

The present invention seeks to provide a means for reducing the track noise emitted by a rail system. It therefore provides a damper for a rail, comprising at least one deformable material attachable to a surface of the rail and incorporating a plurality of elongate resonant members, the resonant members being of a stiff material as compared to the deformable material and being sized to form a resonant system with at least two resonances in

the frequency range where rail vibration is to be reduced.

It is preferred if the resonant members are of different profile, as this provides an easy way of tuning to two different frequencies. However, this can still be achieved with identical profiles. They are suitably embedded in the deformable material, as this both ensures adequate vibrational transfer from the rail to the resonant members and also provides environmental protection. They are ideally more dense than the resilient material. They are suitably of steel or other dense material.

The deformable member is preferably visco-elastic, for example rubber or a rubber-like material. This may be preformed and glued to the rail, or it can be cured in place on the rail.

It is strongly preferred that the damper is positioned on the rail so as to cover the junction between the web and the foot of the rail. This has been found to be exceptionally advantageous in terms of the amount of damping needed to achieve adequate noise reduction. At this position, a damper with at least two resonant frequencies according to the invention can reduce significantly the noise level of the rail. One resonant member can be a elongate angled section, the angle preferably matching the angle between external surfaces of the head and foot. Another resonant member can be a solid elongate block, the external faces adjacent the web and foot being angled to match. Further resonant members can be employed as necessary.

The damper will be easier to manufacture and easier to apply to existing rail if the resonant members are discontinuous within the deformable material. Ideally, the discontinuities in the plurality of resonant members will coincide. It is also possible to apply the damper in discrete sections, leaving gaps (for example) for rail fasteners. However, a continuous length of damper is preferred.

It is preferable for there to be a pair of such dampers, one either side of the rail.

An embodiment of the present invention will now be described, by way of example, with reference to the accompanying Figures in which;

Figure 1 is a vertical section through a rail incorporating dampers being a first embodiment; and

Figure 2 is a vertical section through a rail incorporating dampers being a second embodiment.

Figure 1 shows a vertical section through a rail 10 fitted with a damper according to the present invention. The rail 10 comprises a head 12 which carries the traffic and a narrower web 14 extending downwardly from the head 12 to a foot 16, generally wider than both the head 12 and web 14, on which the rail section rests. In this respect it is a standard rail section.

The junction between the web 14 and the foot 16 is smoothed for fatigue reasons (amongst others), but is essentially a transition from a substantially vertical face to a gently downward sloping top surface of the foot 16. Thus, the angle is somewhat over  $90^\circ$ , usually in the region of  $120^\circ$ .

In this junction, a pair of dampers 18 are provided. One damper 18 is attached on either side. As illustrated, the dampers are identical, which is preferred. Each damper comprises a block of rubber 20 in which is embedded a first resonant member 22 and a second resonant member 24. The first resonant member is an elongate angled member, the angle corresponding to the junction between the head and foot. The second resonant member is an elongate solid section, positioned in the angle of the

first and with two faces at a corresponding angle. The mass per unit length of the first member is greater than the others, significantly so.

Although not visible in Figure 1, the resonant members are discontinuous to allow the damper section to be cut. This eases application of the damper to rail. A suitable maximum length for the sections is 1 metre for application to existing rail.

The top surface of the damper 18 can be profiled to prevent water from building up and seeping into the system.

This arrangement of dampers provides a particularly compact arrangement which is nevertheless able to absorb a wide band of frequencies efficiently from the rail. This frequency band, which may be different for vertical and lateral vibration of the rail, is determined by the resonances of the damper. These resonances are controlled by the choice of mass per unit length of the resonant members and by the surrounding geometry and the physical properties (principally the stiffness) of the material between the resonant members. The width of the frequency band is also determined by the damping properties of the visco-elastic material in the interlayers. The visco-elastic provides a support medium for the resonant members and by its damping properties dissipates vibrational energy. It may be preferable to use different materials for the different interlayers instead of or as well as different thicknesses to obtain the required stiffnesses and thereby affect the resonance frequencies. Positioning the damper at the junction between the web and foot is particularly efficient for absorption, and also avoids interference with passing wheels, track maintenance operations and rail clips. It is also easily accessible for fitting dampers to existing lengths of rail. The compactness of the damper is significant in minimising the noise radiation from the damper itself.

Figure 2 shows a second embodiment of the present invention. Most features of the second embodiment are identical to the first and have therefore been indicated using identical reference numerals. The second embodiment differs only in the construction of the dampers.

According to the second embodiment, first, second and third resonant members 26, 27 and 28 (respectively) are provided. All three in this embodiment consist of an angled metallic member. Each are of different external dimensions so as to resonate at different frequencies. The three are nestled within each other and within the rubber block 20.

The dampers of the present invention could be applied in conjunction with known resilient rail fasteners. This would enable the other advantages of resilient fasteners to be achieved without an unacceptable increase in noise.

Other variations could be made to the embodiments without departing from the scope of the present invention. For example, the resonant members could be arranged end-to-end instead of adjacent as illustrated. They would then be in the same mass of deformable material or in adjacent masses.

CLAIMS


1. A damper for a rail comprising a deformable material attachable to a surface of the rail, the damper incorporating a plurality of elongate resonant members, the resonant members being of a stiff material as compared to the deformable material and being sized to exhibit at least two resonant frequencies in the range of vibration frequencies of the rail.
2. A damper according to claim 1 wherein the resonant members are of a more dense material than the deformable material.
3. A damper according to claim 1 or claim 2 wherein the resonant members are of steel or other metallic material.
4. A damper according to any preceding claim wherein the resonant members are of different profile.
5. A damper according to any preceding claim wherein the resonant members are embedded in the deformable material.
6. A damper according to any preceding claim wherein the deformable member is visco-elastic.
7. A damper according to any preceding claim wherein the deformable member is rubber or rubber-like.
8. A damper according to any preceding claim wherein the deformable material is substantially uniform in composition.
9. A damper according to any preceding claim, preformed and glued to the rail.



10. A damper according to any preceding claim, cured in place on the rail.
11. A damper according to any preceding claim, positioned on the rail so as to cover the junction between the web and the foot of the rail.
12. A damper according to any preceding claim in which at least one resonant member is a elongate angled section.
13. A damper according to claim 12 in which the angle matches the angle between external surfaces of the head and foot.
14. A damper according to any preceding claim in which one of the resonant members is a solid elongate block.
15. A damper according to any preceding claim in which the resonant members are discontinuous within the deformable material.
16. A damper according to claim 15 in which the discontinuities in the plurality of resonant members coincide.
17. A rail to which a damper according to any preceding claim is attached on both sides thereof.
18. A damper substantially as herein described with reference to and/or as illustrated in the accompanying Figures.


1/2

Fig 1



2/2

Fig 2



# INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 98/02767

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 355 578 A (RAQUET ERWIN) 26 October 1982 see column 2, line 59 - column 4, line 13; figures ---	1-3,5-8
A	US 4 364 594 A (RAQUET ERWIN) 21 December 1982 see abstract see column 3, line 4 - column 4, line 39; figures -----	1-3,6-8

# INTERNATIONAL SEARCH REPORT

Information on patent family members

Inter. Appl. Application No

PCT/GB 98/02767

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0628660 A	14-12-1994	NL 9300891 A HU 74133 A	16-12-1994 28-11-1996
DE 3631492 A	17-03-1988	NONE	
EP 0761879 A	12-03-1997	FR 2738263 A	07-03-1997
US 4355578 A	26-10-1982	DE 2816561 A AT 366323 B AT 258479 A BE 875576 A CA 1149840 A CH 645174 A FR 2423687 A GB 2021501 A, B JP 1259544 C JP 54140065 A JP 59033775 B NL 7902622 A SE 7903282 A	18-10-1979 13-04-1982 15-08-1981 31-07-1979 12-07-1983 14-09-1984 16-11-1979 05-12-1979 12-04-1985 30-10-1979 17-08-1984 19-10-1979 18-10-1979
US 4364594 A	21-12-1982	DE 2835020 A AT 367689 B AT 527779 A BE 878166 A CA 1147374 A CH 645441 A FR 2433136 A GB 2027844 A, B JP 55025696 A NL 7905793 A	17-04-1980 26-07-1982 15-12-1981 03-12-1979 31-05-1983 28-09-1984 07-03-1980 27-02-1980 23-02-1980 12-02-1980